

Specifications

LiteDome

- The LiteDome is designed for strobe lights using a Photoflex Strobe Connector.
- The inner baffle eliminates hot spots. (Not available in XSmall and Small)
- The front diffusion face and inner baffle are removable to accommodate lighting from high-contrast to very soft.
- QRC™ (Quick Release Corners) make set-up and break-down quick and easy (Medium, Large, and XLarge only).
- Aluminum-tipped steel support rods offer strength and durability.
- Extensive Quality Control process ensures a perfect product.
- Our soft boxes come with their own Carry Bag for easy transport and storage.

The LiteDome is available in five sizes.

All Photoflex soft boxes require a connector (not included).



NOTE: Maximum wattage for strobe modelling light is 500 watts.

X-SMALL LiteDome

Dimensions

Diffusion Face

Inner baffle

Steel Rods

Carry bag

XT-20XTXS

12x16x9" (30x41x23cm)

RR-FACEXS

N/A

RR-XS

RR-D0MEBAGXS

SMALL LiteDome

Dimensions

Diffusion Face

Inner Baffle

Steel Rods

Carry Bag

XT-1SLD293

16x22x13" (41x56x33cm)

RR-FACES

N/A

RR-S

RR-D0MEBAGSML

MEDIUM LiteDome

Dimensions

Diffusion Face

Inner Baffle

Steel Rods

Carry Bag

XT-2MLD293

24x32x17" (61x81x43cm)

RR-FACEM

RR-BAFFM

RR-MS

RR-D0MEBAGM

LARGE LiteDome

Dimensions

Diffusion Face

Inner Baffle

XT-3LLD293

36x48x25" (91x122x64cm)

RR-FACEL

RR-BAFFL

Steel Rods
Carry Bag

RR-LS
RR-D0MEBAGLG

X-LARGE LiteDome

XT-4XLLD293

Dimensions

54x72x32" (137x183x81cm)

Diffusion Face

RR-FACEXL

Inner Baffle

RR-BAFFXL

Steel Rods

RR-XLA

Carry Bag

RR-D0MEBAGXLG

© 2006 - Photoflex Products Inc