

## Specifications

# MultiDome

- The MultiDome is designed for strobe lights by using a Photoflex Strobe Connector.
- The gold and silver panels offer various degrees of light output warmth.
- The inner baffle eliminates hot spots (not available in Small).
- The front diffusion face and inner baffle are removable to accommodate lighting from high-contrast to very soft.
- QRC™ (Quick Release Corners) make set-up and break-down quick and easy (Medium, Large, and XLarge only).
- Aluminum-tipped steel support rods offer strength and durability.
- Extensive Quality Control process ensures a perfect product.
- Our softboxes comes with their own Carry Bag for easy transport and storage.

The MultiDome is available in four sizes.

All Photoflex soft boxes require a connector (not included).



NOTE: Maximum wattage for strobe modelling light is 500 watts.

---

### SMALL MultiDome

#### MD-1S293

Dimensions

16x22x13" (41x56x33cm)

Diffusion Face

RR-FACES

Inner Baffle

N/A

Circle Mask

RR-CIRCLES

Steel Rods

RR-S

Carry Bag

RR-DOME BAGSML

---

### MEDIUM MultiDome

#### MD-2M293

Dimensions

24x32x17" (61x81x43cm)

Diffusion Face

RR-FACEM

Inner Baffle

RR-BAFFM

Circle Mask

RR-CIRCLEMED

Steel Rods

RR-MS

Carry Bag

RR-DOME BAGM

---

### LARGE MultiDome

#### MD-3L293

Dimensions

36x48x25" (91x122x64cm)

Diffusion Face

RR-FACEL

Inner Baffle

RR-BAFFL

Circle Mask

RR-CIRCLEL

Steel Rods

RR-LS

Carry Bag

RR-DOME BAGLG

---

### X-LARGE MultiDome

#### MD-4XL293

Dimensions

54x72x32" (137x183x81cm)

Diffusion Face

RR-FACEXL

Inner Baffle

RR-BAFFXL

Steel Rods

RR-XLA

Carry Bag

RR-D0MEBAGXLG

© 2006 - Photoflex Products Inc