



specifications

Technical Specifications Hexar RF

Type	35mm interchangeable lens rangefinder focal-plane shutter camera
Format	24 x 36mm
Lens	M-HEXANON lenses (28mm/f2.8, 50mm/f2, 90mm/f2.8). Konica KM bayonet mount.
Shutter	Electronic vertical focal-plane shutter (16 - 1/4000 sec). Speed: Auto 16 - 1/4000 sec; Manual: B, 1, 1/2, 1/4, 1/8, 1/15, 1/30, 1/60, 1/125, 1/250, 1/500, 1/1000, 1/2000, 1/4000 sec.
Film Speed	Automatically sets for ISO 25-5000 DX-coded films; manual setting for ISO 6-6400 films.
Viewfinder	Real image, reverse Galilean. 0.6 x magnification. Split-image, double-image superimposing rangefinder. Viewing frame: automatic bright-frame conversion; compatible with 28, 35, 50, 75, 90, 135mm; automatic parallax compensation (infinity-0.7m).
Flash	Direct X contact; synchronises at less than 1/125 sec.; Flash synchronisation speed: 1/125 sec. with AE, less than 1/125 sec. with manual exposure.
Exposure	Auto-exposure system: Aperture-priority AE or manual, selectable using shutter dial; AE lock possible.
Exposure Adjustment (ISO 100)	+2EV to -2EV, 1/3 step
Film Transport	Automatic advance (during continuous shooting 2.5 frames per sec.), rewinding and mid-roll rewinding possible (Turning off the main switch halts rewinding midway). Rewind time: approx. 13 sec (36-exposure film).
Display Panel	LED viewfinder display: shutter speed (1/4 - 1/4000 sec., 1EV step); Exposure compensation mark.
Power Source	Two 6v Lithium batteries (CR 2)
Battery Life	Approx. 140 rolls (36- exposure film)
Dimensions (W x H x D)	139.5 x 80 x 35mm
Weight	560g (excluding battery)
Other Features	TTL real aperture photometry (centre-weighted light reading); Self -timer; direct-contact accessory shoe; cable release socket.

Notes:

Performance based on Konica test results. Specifications and appearance subject to change without notice.

