

mecablitz 45 CL-4 digital Data sheet

Guide number with ISO 100/21° (35mm)		45
SCA 3002-System		with SCA 3045
SCA 300-System		with SCA 300 A or SCA 3045
E-TTL flash control		✓
3D multisensor fill-in flash		✓
D-TTL flash control		✓
D-TTL/3D multi-sensor fill-in flash		✓
i-TTL-/i-TTL-BL-flash control		✓
Clip-on wide-angle attachment		✓
Illumination above ... mm		28
Secondary reflector		✓
Tilt and swivel reflector	vertical in °	+90
Rotation area	Horizontal in °	360
LCD or LED display		LED
Manual flash mode		✓
Tele-computer apertures		6
TTL mode		✓
Lighting Control Indicator		✓
Possible power sources	Rechargeable battery	✓
	Alkaline mangan battery	✓
	Power pack	✓
Flash recovery time (in sec. ca.)	Alkaline mangan batteries min.	0.3
	Alkaline mangan batteries max.	4
	Power pack min.	0.3
	Power pack P50 max.	3
	NiMH-rechargeable max.	0.3
	NiMH rechargeable max.	4
Min. number of flashes by full light output	NiMh rechargeable 1600 mAh	200
	Alkaline Mangan battery	170
	Power pack P50	300
Weight without batteries in gram (ca.)	Head	680
Dimensions in mm (ca.)	Width	L 92
		C/G
	Height	L 247
		C/G
Depth	L 102	
	C/G	

L = Lamp pole
C = Control Unit
G = Generator