

Metz mecablitz 60 CT-4 D

Technical Details:

| | | | |
|---|-----------------|------|------|
| Guide number by ISO 100/21° and 35 mm | | 60 | |
| Guide number by ISO 100/21° and max. Zoom | | | |
| SCA 3002-system | | | |
| SCA 3000-system | | | |
| SCA 300-system | | Yes | |
| Motor zoom | | | |
| Extended zoom | | | |
| Manual zoom | | | |
| Secondary reflector | | Yes | |
| Swivel reflector-rotation range | vertical in ° | +90 | |
| | horizontal in ° | 360 | |
| Integrated AF measuring beam | | | |
| LCD or LED Display | | LED | |
| IGBT light control | | | |
| Thyristor light control | | Yes | |
| Manual flash operation | | Yes | |
| Tele-computer apertures | | 8 | |
| TTL mode | | Yes | |
| Winder mode | | Yes | |
| Motor drive mode | | Yes | |
| Stroboscopic mode | | | |
| Wireless TTL/automatic operation | | | |
| Partial light output levels | | 25 | |
| Programme memory | | | |
| Key-Function | | Yes | |
| Rapid mode | | | |
| TTL EASY mode | | | |
| Modelling Light | | | |
| Slave-Function | | | |
| Buzzer | | Yes | |
| Flash bracketing with TTL and automatic flash operation | | | |
| Possibility to lock the keys (extended key function) | | | |
| Flash exposure control indicator | | Yes | |
| Battery tester | | | |
| Battery warning indicator | | | |
| Automatic unit cut-off | | | |
| Clip-on wide-angle diffuser | | Yes | |
| Illumination above ... mm | | 28 | |
| Possible power sources | NiCad - bat. | Yes | |
| | Alkaline - bat. | Yes | |
| | Lithium Battery | | |
| | Power Pack | | |
| | Mains operation | Yes | |
| | NiCad - bat. | min. | 0,25 |
| | | max. | 5 |
| | Alkaline - bat. | min. | 0,25 |
| | | max. | 5 |

| | | | |
|--|---------------------|------------------------|------|
| Flash recycle time (in sec. approx.) | Lithium | min. | |
| | | max. | |
| | Power Pack | min. | |
| | | max. | |
| | NiMh-Rechargeable | min. | |
| | | max. | |
| Number of flashes with full light output (approx.) | Dryfit-Rechargeable | min. | 160 |
| | Alkaline - bat. | min. | 80 |
| | Lithium | min. | |
| | Power Pack | min. | |
| | NiMh-Rechargeable | min. | |
| Weight without batteries in g. (approx.) | Handle mount | | 650 |
| | (Control unit/gen.) | | 1850 |
| Dimensions in mm (approx.) | W | Handle mount | 111 |
| | | (Control unit/gen.) | 165 |
| | H | Handle mount | 254 |
| | | (Control unit/gen.) | 126 |
| | D | Handle mount | 102 |
| | | (Control unit/gen.) | 58 |